WINSTAR Display

OLED SPECIFICATION

Model No:

WEO009664B


WINSTAR DISPLAY CO.; LTD

General Specification

Item	Dimension	Unit
Dot Matrix	96 x 64 Dots	—
Module dimension	29.00 x 22.50 x 1.65	mm
Active Area	22.53 x 15.01	mm
Pixel Size	0.205 x 0.205	mm
Pixel Pitch	0.235 x 0.235	mm
Display Mode	Passive Matrix	
Display Color	Monochrome	
Drive Duty	1/64 Duty	
IC	SSD1327	
Interface	4-Wire SPI, I2C, 6800, 8080	
Size	1.1 inch	


WINSTAR DISPLAY CO.,LTD

Contour Drawing & Block Diagram



DOTS SIZE
SCALE 10/1

PIN No.	SYMBOL	PIN No.	SYMBOL
1	VSS	13	R/W#
2	VCC	14	E
3	VCOMH	15	D0
4	VCI	16	D1
5	VDD	17	D2
6	BS1	18	D3
7	BS2	19	D4
8	VSS	20	D5
9	IREF	21	D6
10	CS#	22	D7
11	RES#	23	VCC
12	D/C#	24	VSS



SEG & COM Layout

The non-specified tolerance of dimension is ±0.3 mm .

WINSTAR DISPLAY CO., LTD

Interface Pin Function

<table>
<tr><th>No.</th><th>Symbol</th><th>Function</th></tr>
<tr><td>1</td><td>VSS</td><td>Ground pin. It must be connected to external ground.</td></tr>
<tr><td>2</td><td>VCC</td><td>Power supply for panel driving voltage. This is also the most positive power voltage supply pin. It is supplied by external high voltage source.</td></tr>
<tr><td>3</td><td>VCOMH</td><td>COM signal deselected voltage level.
A capacitor should be connected between this pin and VSS. No external power supply is allowed to connect to this pin.</td></tr>
<tr><td>4</td><td>VCI</td><td>Low voltage power supply and power supply for interface logic level. It should match with the MCU interface voltage level and must be connected to external source.
VCI must always set to be equivalent to or higher than VDD.</td></tr>
<tr><td>5</td><td>VDD</td><td>Power supply pin for core logic operation.</td></tr>
<tr><td>6</td><td>BS1</td><td rowspan="2">MCU bus interface selection pins. Select appropriate logic setting as described in the following table. BS2, BS1 and BS0 are pin select.
Bus Interface selection
<table>
<tr><td>BS[2:1]</td><td>Interface</td></tr>
<tr><td>00</td><td>4 line SPI</td></tr>
<tr><td>01</td><td>I2C</td></tr>
<tr><td>11</td><td>8-bit 8080 parallel</td></tr>
<tr><td>10</td><td>8-bit 6800 parallel</td></tr>
</table>
Note (1) 0 is connected to VSS (2) 1 is connected to VCI</td></tr>
<tr><td>7</td><td>BS2</td></tr>
<tr><td>8</td><td>VSS</td><td>Ground pin. It must be connected to external ground.</td></tr>
<tr><td>9</td><td>IREF</td><td>This pin is the segment output current reference pin</td></tr>
<tr><td>10</td><td>CS#</td><td>This pin is the chip select input connecting to the MCU.
The chip is enabled for MCU communication only when CS# is pulled LOW (active LOW).</td></tr>
<tr><td>11</td><td>RES#</td><td>This pin is reset signal input.
When the pin is pulled LOW, initialization of the chip is executed.
Keep this pin pull HIGH during normal operation.</td></tr>
<tr><td>12</td><td>D/C#</td><td>This pin is Data/Command control pin connecting to the MCU.
When the pin is pulled HIGH, the data at D[7:0] will be interpreted as data.
When the pin is pulled LOW, the data at D[7:0] will be transferred to a command register.
In I2C mode, this pin acts as SA0 for slave address selection.
When 3-wire serial interface is selected, this pin must be connected to VSS.</td></tr>
<tr><td>13</td><td>R/W#</td><td>This pin is read / write control input pin connecting to the MCU interface.
When 6800 interface mode is selected, this pin will be used as Read/Write (R/W#) selection input. Read mode will be carried out when this pin is pulled HIGH and write mode when LOW.
When 8080 interface mode is selected, this pin will be the Write (WR#) input. Data write operation is initiated when this pin is pulled LOW and the chip is selected.</td></tr>
</table>

WINSTAR DISPLAY CO.,LTD

14	E	This pin is MCU interface input. When 6800 interface mode is selected, this pin will be used as the Enable (E) signal. Read/write operation is initiated when this pin is pulled HIGH and the chip is selected. When 8080 interface mode is selected, this pin receives the Read (RD#) signal. Read operation is initiated when this pin is pulled LOW and the chip is selected. When serial or I2C interface is selected, this pin must be connected to VSS.
15	D0	These pins are bi-directional data bus connecting to the MCU data bus. Unused pins are recommended to tie LOW. When serial interface mode is selected, D0 will be the serial clock input: SCLK; D1 will be the serial data input: SDIN and D2 should be kept NC. When I2C mode is selected, D2, D1 should be tied together and serve as SDAout, SDAin in application and D0 is the serial clock input, SCL.
16	D1	
17	D2	
18	D3	
19	D4	
20	D5	
21	D6	
22	D7	
23	VCC	Power supply for panel driving voltage. This is also the most positive power voltage supply pin. It is supplied by external high voltage source.
24	VSS	Ground pin.

WINSTAR DISPLAY CO.,LTD

Absolute Maximum Ratings

Parameter	Symbol	Min	Max	Unit
Supply Voltage for Operation	VCI	-0.3	4.0	V
Supply Voltage for Logic	VDD	-0.5	2.75	V
Supply Voltage for Display	VCC	-0.5	19.0	V
Operating Temperature	TOP	-40	+80	°C
Storage Temperature	TSTG	-40	+85	°C

Electrical Characteristics

DC Electrical Characteristics

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage for Logic	VCI	—	2.8	3.0	3.3	V
Supply Voltage for Display	VCC	—	8.0	8.5	9.0	V
Input High Volt.	VIH	—	0.8×VCI	—	VCI	V
Input Low Volt.	VIL	—	VSS	—	0.2×VCI	V
Output High Volt.	VOH	—	0.9×VCI	—	VCI	V
Output Low Volt.	VOL	—	VSS	—	0.1×VCI	V
50% Check Board operating Current	ICC	VCC=8.5V	—	13.0	26.0	mA

WINSTAR DISPLAY CO.,LTD