Represented by:

FIRST Components s.r.l.
www.first-components.com
technical@first-components.com
+39 0332 1888005

WINSTAR Display

OLED SPECIFICATION

Model No:

WEO12864X#AHXXXXXXXX-FC


WINSTAR DISPLAY CO., LTD

General Specification

Item	Dimension	Unit
Dot Matrix	128 x 64	—
Module dimension	42.04 × 27.22 × 1.41	mm
Active Area	35.05 × 17.51	mm
Pixel Size	0.249 × 0.249	mm
Pixel Pitch	0.274 × 0.274	mm
Display Mode	Passive Matrix	
Display Color	Monochrome	
Drive Duty	1/64 Duty	
IC	SH1106	
Interface	6800,8080,4-wire SPI,I2C	
Size	1.54 inch	

WINSTAR DISPLAY CO.,LTD
first components

Contour Drawing & Block Diagram



PIN	SYMBOL
1	ESD_GND
2	VSS
3	VSS
4	NC
5	VDD1
6	IM1
7	IM2
8	$\overline{CS}$
9	$\overline{RES}$
10	A0
11	$\overline{WR}$
12	E/$\overline{RD}$
13	D0
14	D1
15	D2
16	D3
17	D4
18	D5
19	D6
20	D7
21	IREF
22	VCOMH
23	VPP
24	ESD_GND

The non-specified tolerance of dimension is ±0.3 mm .

INSTAR DISPLAY CO., LTD
components

Interface Pin Function

<table>
<tr><th>No.</th><th>Symbol</th><th>Function</th></tr>
<tr><td>1</td><td>ESD_GND</td><td>ESD Ground pin</td></tr>
<tr><td>2</td><td>VSS</td><td>Ground.</td></tr>
<tr><td>3</td><td>VSS</td><td>Ground.</td></tr>
<tr><td>4</td><td>NC</td><td>No connection</td></tr>
<tr><td>5</td><td>VDD1</td><td>Power supply input</td></tr>
<tr><td>6</td><td>IM1</td><td rowspan="2">These are the MPU interface mode select pads.
<table>
<tr><td></td><td>8080</td><td>I2C</td><td>6800</td><td>4-wire SPI</td></tr>
<tr><td>IM1</td><td>1</td><td>1</td><td>0</td><td>0</td></tr>
<tr><td>IM2</td><td>1</td><td>0</td><td>1</td><td>0</td></tr>
</table>
Note
(1) 0 is connected to VSS
(2) 1 is connected to VDD1</td></tr>
<tr><td>7</td><td>IM2</td></tr>
<tr><td>8</td><td>$\overline{CS}$</td><td>This pad is the chip select input. When $\overline{CS}$ = “L”, then the chip select becomes active, and data/command I/O is enabled.</td></tr>
<tr><td>9</td><td>$\overline{RES}$</td><td>This is a reset signal input pad. When $\overline{RES}$ is set to “L”, the settings are initialized. The reset operation is performed by the $\overline{RES}$ signal level.</td></tr>
<tr><td>10</td><td>A0</td><td>This is the Data/Command control pad that determines whether the data bits are data or a command.
A0 = “H”: the inputs at D0 to D7 are treated as display data.
A0 = “L”: the inputs at D0 to D7 are transferred to the command registers.
In I2C interface, this pad serves as SA0 to distinguish the different address of OLED driver.</td></tr>
<tr><td>11</td><td>$\overline{WR}$
(R/$\overline{W}$)</td><td>This is a MPU interface input pad.
When connected to an 8080 MPU, this is active LOW. This pad connects to the 8080 MPU $\overline{WR}$ signal. The signals on the data bus are latched at the rising edge of the $\overline{WR}$ signal.
When connected to a 6800 Series MPU: This is the read/write control signal input terminal.
When R/$\overline{W}$ = “H”: Read.
When R/$\overline{W}$ = “L”: Write.</td></tr>
<tr><td>12</td><td>E/$\overline{RD}$</td><td>This is a MPU interface input pad.
When connected to an 8080 series MPU, it is active LOW. This pad is connected to the $\overline{RD}$ signal of the 8080 series MPU, and the data bus is in an output status when this signal is “L”.
When connected to a 6800 series MPU, this is active HIGH. This is used as an enable clock input of the 6800 series MPU.
When $\overline{RD}$ = “H”: Enable.</td></tr>
</table>

WINSTAR DISPLAY CO., LTD

		When $\overline{RD}$ = “L”: Disable.
13-20	D0~D7	This is an 8-bit bi-directional data bus that connects to an 8-bit or 16-bit standard MPU data bus. When the serial interface is selected, then D0 serves as the serial clock input pad (SCL) and D1 serves as the serial data input pad (SI). At this time, D2 to D7 are set to high impedance. When the I2C interface is selected, then D0 serves as the serial clock input pad (SCL) and D1 serves as the serial data input pad (SDAI). At this time, D2 to D7 are set to high impedance.
21	IREF	This is a segment current reference pad. A resistor should be connected between this pad and VSS. Set the current at 18.75uA.
22	VCOMH	This is a pad for the voltage output high level for common signals. A capacitor should be connected between this pad and VSS.
23	VPP	OLED panel power supply. Generated by internal charge pump. Connect to capacitor. It could be supplied externally.
24	ESD_GND	ESD Ground pin

WINSTAR DISPLAY CO.,LTD
first components

Absolute Maximum Ratings

Parameter	Symbol	Min	Max	Unit
Supply Voltage for Logic	VDD1	-0.3	3.6	V
Supply Voltage for Display	VPP	-0.3	14.5	V
Operating Temperature	TOP	-40	+80	°C
Storage Temperature	TSTG	-40	+85	°C

Electrical Characteristics

DC Electrical Characteristics

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage for Logic	VDD1	–	1.65	3.0	3.3	V
Supply Voltage for Display	VPP	–	6.4	12.5	13.0	V
High Level Input	VIH	–	0.8×VDD1	–	VDD1	V
Low Level Input	VIL	–	VSS	–	0.2×VDD1	V
High Level Output	VOH	–	0.8×VDD1	–	VDD1	V
Low Level Output	VOL	–	VSS	–	0.2×VDD1	V
Display 50% Pixel on	IPP	VPP =12.5V	–	13	20	mA

WINSTAR DISPLAY CO., LTD
First Components