Winstar Display Co., LTD
華凌光電股份有限公司
WEB: http://www.winstar.com.tw E-mail: winstar@winstar.com.tw

SPECIFICATION

MODULE NO.: WF35-320240RD#000-FC

General Specifications

Item	Dimension	Unit
Size	3.5	inch
Dot Matrix	320 x RGBx240(TFT)	dots
Module dimension	76.84(W) x 63.84(H) x 3.27(D)	mm
Active area	70.08 x 52.56	mm
Dot pitch	0.073 x 0.219	mm
LCD type	TFT, Normally White, Transmissive	
View Direction	12 o'clock	
Gray Scale Inversion Direction	6 o'clock	
Backlight Type	LED,Normally White	
IC	SSD2119	
With /Without TP	Without TP	
Surface	Anti-Glare	

*Color tone slight changed by temperature and driving voltage.

WINSTAR DISPLAY CO., LTD

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	℃
Storage Temperature	TST	-30	—	+80	℃

Electrical Characteristics

Item	Symbol	MIN	TYP	MAX	Unit
Power supply voltage	V_{CI}	2.5	3.3	3.6	V
Power supply pin of IO pins	V_{DDIO}	1.4	3.3	3.6	V
Current consumption	IVCI+IVDDIO	-	-	10	mA
Dot clock	DCK	-	5.5	8.2	MHz


WINSTAR DISPLAY CO.,LTD

Interface

No.	Symbol	Description
1	VCI	Booster input voltage pin
2	VCI	Booster input voltage pin
3	VSS	Ground
4	VDDIO	Voltage input pin for logic
5	VSS	Ground
6	RESET	Reset Signal pin (“Low” is enable)
7	DC/SDC	Data or Command select PIN.
8	E/RD	6800 system: E(enable signal) 8080 system : RD(read strobe signal) Serial mode: Not use and should be connected to VDDIO or VSS
9	WR	6800 system : RW (indicates read cycle when high ,write cycle when low) 8080 system : WR (write strobe signal)
10	CS	Chip select
11	SCL	Serial Clock.
12	SD0	Serial Data output
13	SDI	Serial Data Input
14	WSYNC	Ram write synchronization output. Leave it OPEN when not used.
15~32	D17~D0	Data bus
33	VSS	Ground
34	DOTCLK	Dot-clock signal and oscillator source
35	HSYNC	Line Synchronous Signal
36	VSYNC	Frame Synchronous Signal
37	DE	Display enable pin for controller
38	VSS	Ground
39	PS0	Interface select PIN
40	PS1	
41	PS2	
42	PS3	
43	VSS	Ground
44~47	NC	NC
48	VSS	Ground
49	LEDK	Backlight LED Cathode
50	LEDA	Backlight LED Anode.

WINSTAR DISPLAY CO.,LTD

Contour Drawing



SCALE 50/1

PIN NO.	SYMBOL	PIN NO.	SYMBOL
1	VCI	26	D6
2	VCI	27	D5
3	VSS	28	D4
4	VDDIO.	29	D3
5	VSS	30	D2
6	RESET	31	D1
7	DC/SDC(RS)	32	D0
8	E/RD	33	VSS
9	WR	34	DOTCLK
10	CS	35	HSYNC
11	SCL	36	VSYNC
12	SDO	37	DE
13	SDI	38	VSS
14	WSYNC(NC)	39	PS0
15	D17	40	PS1
16	D16	41	PS2
17	D15	42	PS3
18	D14	43	VSS
19	D13	44	NC
20	D12	45	NC
21	D11	46	NC
22	D10	47	NC
23	D9	48	VSS
24	D8	49	LEDK
25	D7	50	LEDA

The non-specified tolerance of dimension is ±0.3mm.

WINSTAR DISPLAY CO., LTD