

The drawing contained herein is the exclusive property of WiseChip. It is not allowed to copy, reproduce and or disclose in any formats without permission of WiseChip.

Item	Date	Remark
A	20120730	Original Drawing










(Reference Mechnical Design)



Pin	Symbol
1	N.C.
2	VSL
3	VSS
4	REGVDD
5	SHLC
6	SHLS
7	VDD
8	VDDIO
9	BS0
10	BS1
11	BS2
12	GPIO
13	CS#
14	RES#
15	D/C#
16	R/W#(WR#)
17	E(RD#)
18	D0
19	D1
20	D2
21	D3
22	D4
23	D5
24	D6
25	D7
26	IREF
27	ROM0
28	ROM1
29	OPR0
30	OPR1
31	VCOMH
32	VCC
33	N.C.

Notes:

1. Color: Light Blue
2. Driver IC: US2066
3. FPC Number:UT-1066-P04
4. Interface:
   4-/8-bit 68XX/80XX Parallel, SPI, I2C
5. General Tolerance: ±0.30
6. The total thickness (2.10 Max) is without polarizer protective film & remove tape.
   The actual assembled total thickness with above materials should be 2.35 Max.

Customer Approval Signature	WiseChip Semiconductor Inc.						Drawing Number	Rev.
							DMX1602SDGF20	A
	Unless Otherwise Specified		Title	UC-1602ALBEG01 Folding Type OEL Display Module Pixel Number: Character 16 x 2, Monochrome, COG Package			Material	
	Unit	mm					Soda Lime / Polyimide	
	General Roughness							
	Tolerance			Drawn	E.E.	Panel / E.	P.M.	
	Dimension	±0.3	By	Dora Yang	Ting Kuo Hu	Ivy Lo	Kate Chung	Scale: 1:1 / Sheet: 1 of 1 / Size: A3
	Angle	±1	Date	20120730	20120730	20120730	20120730	