SMART DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司

Represented by:

FIRST Components s.r.l.
www.first-components.com
technical@first-components.com
+39 0332 1888005

Winstar Display Co., LTD
華凌光電股份有限公司
WEB: https://www.winstar.com.tw E-mail: sales@winstar.com.tw

SPECIFICATION

CUSTOMER : _____

MODEL NO. : WL0F00043000WGFAASA00-FC

APPROVED BY: (FOR CUSTOMER USE ONLY)	

SALES BY	APPROVED BY	CHECKED BY	PREPARED BY
	Ginger Xu	蕭宏欣	Jason Chan

VERSION	DATE	REVISED PAGE NO.	SUMMARY
0	2024/08/09		First issue

Contents

1. Records of Revision
2. Summary
3. Product information
4. Contour Drawing
5. Absolute Maximum Ratings
6. Electrical Characteristics
7. BOM
8. Block diagram
9. Interface
10. Reliability

first FC components

Winstar Display Co., LTD
華凌光電股份有限公司

MODLE NO：
WL0F00043000WGFAASA00-FC

RECORDS OF REVISION			DOC. FIRST ISSUE
VERSION	DATE	REVISED PAGE NO.	**SUMMARY**
0	2024/08/09		First issue

first FC components

Summary

4.3 Inch Smart Display (UART series) Feature

1. Input voltage dynamic range 5V to 28V, typical voltage 12V.
2. Self-testing after booting function.
3. UART communication interface.
4. Supports UART protocol, default baud rate at 115200Kbps.
5. Built in flash memory, store the fonts and pictures.
6. Support capacitive touch panel (CTP).
7. Embedded buzzer function.
8. Demo set HOST can be used on multiple platforms, such as Computer (with USB to UART Dongle), MCU, Raspberry Pi (with PiCAN2).
9. GPIO PIN support. Supports 8 channel Bi-direction GPIOs with TTL 3.3V logic level. The setting functions through PC tools, Smart Display GUI Builder.

first FC components

Product information

General information

Item	Standard Value	Unit
Operating voltage	5-28	Vdc
Communication Interface	UART	--
MCU	STM32F750	N/A
Flash Memory	16	MB
LCD display size	4.3	inch
Dot Matrix	480× 3(RGB) × 272	dot
Module dimension	119.3(W) ×67.2(H) ×13 (D)	mm
Active area	95.04(W) × 53.856 (H)	mm
Pixel pitch	0.198(H) x 0.198(V)	mm
Brightness	Min: 300; Typ: 400	cd/m^2
LCD type	TFT, Normally Black, Transmissive	
View Direction	80/80/80/80	
Aspect Ratio	16:9	
With /Without TP	With CTP	
Surface	Glare	

first components


Contour Drawing

CON2

PIN	SYMBOL	PIN	SYMBOL
1	VIN	9	VBUS
2	GND	10	UART_RX
3	Reserve	11	UART_TX
4	Reserve	12	GND
5	GND	13	VIN
6	GND	14	Reserve
7	Reserve	15	Reserve
8	Reserve	16	GND

CON3

PIN	SYMBOL	PIN	SYMBOL
1	+3V3	9	IO_0
2	SWCLK	10	IO_1
3	GND	11	IO_2
4	SWDIO	12	IO_3
5	NRST	13	IO_4
6	GND	14	IO_5
7	WKUP	15	IO_6
8	BOOT0	16	IO_7



The non-specified tolerance of dimension is ±0.3mm.

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-30	—	+80	℃
Storage Temperature	TST	-30	—	+80	℃
Supply Voltage	VIN			+30	V

Note: Device is subject to be damaged permanently if stresses beyond those absolute maximum ratings listed above
1. Temp. ≦60℃, 90% RH MAX. Temp.＞60℃, Absolute humidity shall be less than 90% RH at 60℃

Electrical Characteristics


Item	Symbol	Min	Typ	Max	Unit	Note
Supply Voltage	VCC	5	12	28	V	
Supply Current	ICC		180		mA	
I/O pin Voltage	--	--	--	3.3	V	Note 1

Note1: Exceed 3.3V may cause MCU damage.

BOM

Item	Description	Remark
LCM	WF43-480272WD#APW3-FC	
PCBA	SV10004R300WB00N0101	

Block diagram



Interface

CON2 definition:

Pin	Symbol	Function	Remark
16	GND	Power GND	Input
15	Reserved	--	--
14	Reserved	--	--
13	VIN	Power +5V~+28V	Input
12	GND	Power GND	Input
11	UART1_TX		output
10	UART1_RX		Input
9	VBUS	Power	Input
8	Reserved	--	--
7	Reserved	--	--
6	GND	Power GND	Input
5	GND	Power GND	Input
4	Reserved	--	--
3	Reserved	--	--
2	GND	Power GND	Input
1	VIN	Power +5V~+28V	Input

CON3 definition:

Pin	Symbol	Function	Remark
16	IO_7	GPIO (PC5)	I/O
15	IO_6	GPIO (PC4)	I/O
14	IO_5	GPIO (PC1)	I/O
13	IO_4	GPIO (PF9)	I/O
12	IO_3	GPIO (PB5)	I/O
11	IO_2	GPIO (PB4)	I/O
10	IO_1	GPIO (PD5)	I/O
9	IO_0	GPIO (PD4)	I/O
8	BOOT0	--	Input
7	WKUP	Wake UP (PA0)	Input
6	GND	GND for SWD interface	Output
5	NRST	Reset pin for SWD interface	Input

first components

4	SWDIO	Data pin for SWD interface	I/O
3	GND	GND for SWD interface	Output
2	SWCLK	CLK pin for SWD interface	Input
1	+3V3	3.3V power for SWD interface	Output

first FC components

Reliability

Content of Reliability Test (Wide temperature, -30℃~80℃)

Environmental Test			
Test Item	Content of Test	Test Condition	Note
High Temperature storage	Endurance test applying the high storage temperature for a long time.	80℃ 200hrs	2
Low Temperature storage	Endurance test applying the low storage temperature for a long time.	-30℃ 200hrs	1,2
High Temperature Operation	Endurance test applying the electric stress (Voltage & Current) and the thermal stress to the element for a long time.	80℃ 200hrs	
Low Temperature Operation	Endurance test applying the electric stress under low temperature for a long time.	-30℃ 200hrs	1
High Temperature/ Humidity Operation	The module should be allowed to stand at 60℃,90%RH max	60℃,90%RH 96hrs	1,2
Thermal shock resistance	The sample should be allowed stand the following 10 cycles of operation -30℃ 25℃ 80℃ 30min 5min 30min 1 cycle	-30℃/80℃ 10 cycles	——
Static electricity test	Endurance test applying the electric stress to the terminal.	VS=±2KV~±6KV(contact),±2KV~±8KV(air), RS=330Ω CS=150pF 10 times	——

Note1: No dew condensation to be observed.

Note2: The function test shall be conducted after 4 hours storage at the normal Temperature and humidity after remove from the test chamber.

Check samples by meter V_{IN}, I_{system}

Item	No 1	Note
V_{IN} (V)	12	
I_{System}(mA)	177	