2022-D2-002

T Panel ID204827MC-043ABJ Datasheet

VERSION:1.00
AUGUST, 2022

Immense Oak Technologies

Represented by:

FIRST Components s.r.l.
www.first-components.com
sales@first-components.com
+39 0332 1888005

Any documentation, materials or information including data sheets, app notes, PPT presentation and any other formal documents (“Publication”) that Immense Oak Technologies, Inc.(“IOT”) provides are only for your convenience and reference, and IOT may update its Publication at its sole discretion. IOT will make reasonable efforts to ensure the accuracy and completeness of its Publication but IOT does not represent and warrant the accurate expressions and suggestions of the contents. You agree that IOT shall not be responsible for any losses or damages as a result of or relating to your usage of such Publication.

IOT does not accept any liability for the consequences arising from the application, use, or misuse of any resources contained on or made available through the Publication, including any injury or damage to any person or property as a matter of product liability, negligence, or otherwise. IOT does not guarantee the sequence, accuracy, or completeness of any information or content available in the Publication and shall not be liable in any way to you or anyone else who may use the information or content or to whom the information or content may be furnished, for any delays, inaccuracies, unavailability, errors, or omissions therefrom or in the transmission or delivery of all or any part thereof or for any damage arising therefrom.

Copyright © 2022, Immense Oak Technologies, Inc. All rights reserved.

For Technical Support: support@iot-hmi.com

For Sales Support: sales@iot-hmi.com

Website: https://www.iot-hmi.com/

first FC components

Revision History

Table 1. Revision History

Revision	Description	Release Date
1.00	Initial release	August, 2022

first FC components

Contents

1 Introduction 6

1.1 Features 6

2 Interface Description 7

2.1 Connector 10 (CN10) Pin Definition 8

2.2 Connector 9 (CN9) Pin Definition 10

2.3 DC Power Connector Pin Definition 12

2.4 Connector 5 (CN5) Pin Definition 13

2.5 Connector 3 (J3) Serial Wire Debug (SWD) Pin Definition 14

2.6 USB Micro B Connector (OTG-CN) Pin Definition 15

2.7 Micro SD Card Connector (CN2) Pin Definition 15

3 Absolute Maximum Ratings 16

4 Electrical Characteristics 17

4.1 DC Characteristics 17

5 Mechanical Drawing 18

6 IOT Product Nomenclature 19

first FC components

Figure List

Figure 1. Control Board Outline 7

Figure 2. CN10 Pin Definition 8

Figure 3. CN9 Pin Definition 10

Figure 4. DC Power Connector Pin Definition 12

Figure 5. CN5 Pin Definition 13

Figure 6. J3 Pin Definition 14

Figure 7. Mechanical Drawing for ID204827MC-043ABJ with LCM 18

first FC components

Table List

Table 1. Revision History 2

Table 2. T Panel Product Line 6

Table 3. CN10 Pin Definition 8

Table 4. CN9 Pin Definition 10

Table 5. DC Power Connector Pin Definition 12

Table 6. CN5 Pin Definition 13

Table 7. J3 Pin Definition 14

Table 8. Absolute Maximum Ratings 16

Table 9. DC Characteristic 17

Table 10. IOT Product Naming Rule 19

Table 11. IOT Product Nomenclature 19

Table 12. Field 12 of IOT Product Nomenclature 20

first FC components

1 Introduction

T Panel product line provides total solutions for HMI. These solutions include TouchGFX (provided by STMicroelectronics), control board and LCM. This datasheet is intended to describe the hardware part of the solutions. This document covers the following product:

Table 2. T Panel Product Line

Part Number	Resolution	Panel Size	Touch Type
ID204827MC-043ABJ	480x272	4.3”	CTP

Note: CTP = Capacitive Touch Panel

The product complies with TouchGFX. The LCMs are sourced from our partners. For more details on the LCMs, please contact sales@iot-hmi.com or our local distributors.


1.1 Features


- Comply with TouchGFX for delivering the Smart HMI total solution
- STM32H750 with 32MB DRAM
- Built-in 2Gb (256MB) Flash memory for storage
- Support ARGB888 (16,777,216 colors) with 256 levels of transparency
- Support LCM backlight control
- Support touch control (CTP)
- Support GPIO, PWM, Input-Capture, UART, ADC, DAC, I2S, I2C, SPI and SWD functions based on MCU pin definition (See STM32H750 for details)
- Support RTC with LSE
- Support USB Micro B connector and Micro SD Card slot


first components


2 Interface Description


Figure 1. Control Board Outline











2.1 Connector 10 (CN10) Pin Definition

Figure 2. CN10 Pin Definition




Table 3. CN10 Pin Definition

Pin Number	MCU Pin Name	Name	I/O	Description
0	-	DC5V	P	DC 5V output.
1	-	GND	P	Supply Ground.
2	-	DC3.3V	P	DC 3.3V output.
3	PD11	GPIO1	I/O	General Purpose Input/Output, 3.3V Level - 5V Tolerant.
4	PA15	PWM3	N/A	This pin offers two different functions: GPIO and PWM.
5	PD12	GPIO2	I/O	General Purpose Input/Output, 3.3V Level - 5V Tolerant.
6	PB3	PWM4	I/O	This pin offers two different functions: GPIO and PWM.
7	PD13	GPIO3	I/O	General Purpose Input/Output, 3.3V Level - 5V Tolerant.
8	PH6	PWM5	I/O	This pin shares the same functionality as that of PWM4. Please refer to PWM4 description for details.
9	PA3	GPIO4	I/O	General Purpose Input/Output, 3.3V Level - 5V Tolerant.
10	PC7	PWM6	I/O	This pin shares the same functionality as that of PWM4. Please refer to PWM4 description for details.
11	PD4	GPIO5	I/O	General Purpose Input/Output, 3.3V Level - 5V Tolerant.
12	-	GND	P	Supply Ground.
13				
14	PC2	ADC0	I/O	General Purpose I/O pin with Analog Capability. This pin has a range of 0-3.3V when used as an Analog Input, and is 3.3V tolerant only.

Pin Number	MCU Pin Name	Name	I/O	Description
15	PA6	ADC1	I/O	General Purpose I/O pin with Analog Capability. This pin has a range of 0-3.3V when used as an Analog Input, and is 3.3V tolerant only.
16	PC4	ADC2	I/O	General Purpose I/O pin with Analog Capability. This pin has a range of 0-3.3V when used as an Analog Input, and is 3.3V tolerant only.
17	PB1	ADC3	I/O	General Purpose I/O pin with Analog Capability. This pin has a range of 0-3.3V when used as an Analog Input, and is 3.3V tolerant only.
18	PC0	ADC4	I/O	General Purpose I/O pin with Analog Capability. This pin has a range of 0-3.3V when used as an Analog Input, and is 3.3V tolerant only.
19	PC1	ADC5	I/O	General Purpose I/O pin with Analog Capability. This pin has a range of 0-3.3V when used as an Analog Input, and is 3.3V tolerant only.

Note: I = Input, O = Output, P = Power

first FC components

2.2 Connector 9 (CN9) Pin Definition

Figure 3. CN9 Pin Definition




Table 4. CN9 Pin Definition

Pin Number	MCU Pin Name	Name	I/O	Description
0	-	DC5V	P	DC 5V output.
1	-	DC3.3V	P	DC 3.3V output.
2	-	GND	P	Supply Ground.
3	$\overline{\text{RESET}}$	$\overline{\text{RESET}}$	I	Reset signal. Active low.
4	PH4	I2C_SCL	O	I2C Clock signal.
5	PH5	I2C_SDA	I/O	I2C Data signal.
6	PF7	UART7_TX	I/O	TX for UART Asynchronous Serial Transmit pin, TTL level. Connect this pin to the Receive (Rx) signal of other serial devices. Used in conjunction with the UART_RX pin for communication with external MCU. This pin is tolerant up to 5.0V levels.

Pin Number	MCU Pin Name	Name	I/O	Description
7	PA8	UART7_RX	I/O	RX for UART Asynchronous Serial Receive pin, TTL level. Connect this pin to the Transmit (Tx) signal of other serial devices. Used in conjunction with the UART_TX pin for communication with external MCU. This pin is tolerant up to 5.0V levels.
8	PJ8	UART8_TX	I/O	TX for UART Asynchronous Serial Transmit pin, TTL level. Connect this pin to the Receive (Rx) signal of other serial devices. Used in conjunction with the UART_RX pin for communication with external MCU. This pin is tolerant up to 5.0V levels.
9	PJ9	UART8_RX	I/O	RX for UART Asynchronous Serial Receive pin, TTL level. Connect this pin to the Transmit (Tx) signal of other serial devices. Used in conjunction with the UART_TX pin for communication with external MCU. This pin is tolerant up to 5.0V levels.
10	PA2	PWM1_IC	I/O	This pin offers three different functions: GPIO, PWM and Input-capture.
11	PB0	PWM2_IC	I/O	This pin shares the same functionality as that of PWM1_IC. Please refer to PWM1_IC description for details.

Note: I = Input, O = Output, P = Power

first FC components

2.3 DC Power Connector Pin Definition

Figure 4. DC Power Connector Pin Definition





Table 5. DC Power Connector Pin Definition

Pin Number	MCU Pin Name	Name	I/O	Description
0	-	GND	P	Supply Ground.
1	PB12	UART5_RX	I/O	RX for UART Asynchronous Serial Receive pin, TTL level. Connect this pin to the Transmit (Tx) signal of other serial devices. Used in conjunction with the UART_TX pin for communication with external MCU. This pin is tolerant up to 5.0V levels.
2	PB13	UART5_TX	I/O	TX for UART Asynchronous Serial Transmit pin, TTL level. Connect this pin to the Receive (Rx) signal of other serial devices. Used in conjunction with the UART_RX pin for communication with external MCU. This pin is tolerant up to 5.0V levels.
3	-	+5V	P	DC 5V input.

Note: I = Input, O = Output, P = Power

2.4 Connector 5 (CN5) Pin Definition

Figure 5. CN5 Pin Definition



first FC components


Table 6. CN5 Pin Definition

Pin Number	MCU Pin Name	Name	I/O	Description
0	-	DC3.3V	P	DC 3.3V output.
1	PG10	SPI_CS	O	Serial enable pin. Active low
2	PA5	SPI_CLK	O	Serial Peripheral Interface clock.
3	PB5	SPI_MOSI	I/O	Serial data input/output.
4	PG9	SPI_MISO	I/O	Serial data input/output.
5	-	GND	P	Supply Ground.

Note: I = Input, O = Output, P = Power

2.5 Connector 3 (J3) Serial Wire Debug (SWD) Pin Definition

Figure 6. J3 Pin Definition



first FC components

Table 7. J3 Pin Definition

Pin Number	MCU Pin Name	Name	I/O	Description
0	DC3.3V	DC3.3V	P	DC 3.3V input.
1	SWCLK	SWCLK	I	Serial wire clock.
2	GND	GND	P	Supply Ground.
3	SWDIO	SWDIO	I/O	Serial wire date in/out.

Note: I = Input, O = Output, P = Power

2.6 USB Micro B Connector (OTG-CN) Pin Definition

Standard Pin Definition for USB Micro B Connector (OTG-CN)

2.7 Micro SD Card Connector (CN2) Pin Definition

Standard Pin Definition for Micro SD Card Connector (CN2)

first FC components

3 Absolute Maximum Ratings

Table 8. Absolute Maximum Ratings

Item	Minimum	Maximum	Unit
Storage temperature	-30	+80	°C
Operating ambient temperature	-20	+70	°C
Input supply voltage with respect to GND	+4.75	+5.5	V
IO voltage with respect to GND	+3.3V (± 10%)	+5.0	V

Note: IO Voltage is specified under the no-pull configuration.

first FC components

4 Electrical Characteristics

4.1 DC Characteristics

The following table is measured when the control board is driving a 4.3" LCM @800cd/m^2.


Table 9. DC Characteristic

Symbol	Item	Minimum	Typical	Maximum	Unit
V_{IN}	Input power voltage	4.75	5.0	5.5	V
V_{DD}	Internal working voltage	3.0	3.3	3.5	V
	Operating current @100% backlight	340	360	–	mA
	Operating current @50% backlight	255	270	–	mA
	Operating current with backlight turned off	185	195	–	mA
V_{IH}	I/O input high level	$0.7V_{DD}$	–	5.0	V
V_{IL}	I/O input low level	0	–	$0.3V_{DD}$	V
V_{OH}	I/O output high level	V_{DD}-0.4	–	V_{DD}	V
V_{OL}	I/O output low level	0	–	$0.3V_{DD}$	V

first FC components

5 Mechanical Drawing

Figure 7. Mechanical Drawing for ID204827MC-043ABJ with LCM



6 IOT Product Nomenclature

This section describes IOT's product naming rule.

Table 10. IOT Product Naming Rule

Field	1	2	3	4	5	6	7	8	9	10	11	12	13	14
# of digits	1	2	3	2	1	1	1	1	3	1	1	1	1	1
Example	I	D2	048	27	M	C	X	-	043	A	B	J	-	X

Table 11. IOT Product Nomenclature

Field	# of digits	Description
1	1	I: Representing Immense Oak Technologies' company name.
2	2	D#: Product Line Name. The first digit is an alphabet and the second is a number.
3	3	Supported horizontal resolution with ones digit dropped.
4	2	The higher two digits of the supported vertical resolution.
5	1	Product offering type. M: PCB + TFT LCM P: PCB C: Chipset
6	1	Touch panel type. R: RTP C: CTP N: No touch control.
7	1	Reserved functional identifier. Can be omitted if not needed.
8	1	Separation hyphen.
9	3	TFT LCM dimensional information. 3 digits represent the tens, ones and tenths digit of the LCM diagonal domination in inches. For examples, 10.1" => 101, 4.7" => 047
10	1	Reserved for product serial number or functional identifier.
11	1	Backlight type. S: Viewable under the sun (> 1000cd/m^2) B: Bright backlight (< 1000cd/m^2, > 600cd/m^2) W: Regular backlight (< 600cd/m^2, > 300cd/m^2)
12	1	LCD type and its characteristics. Please refer to Table 12 for details.
13	1	Separation hyphen.
14	1	Reserved.

Note: For the control board part number, Field 7 and beyond are omitted.

Table 12. Field 12 of IOT Product Nomenclature

Transmissive	Panel Type and View Angle		Working Temperature
A	TN	6H	Commercial Grade -10°C ~ 60°C
B		12H	
C		O-film	
D	IPS		
E	VA		
F	TN	6H	Industrial Grade -20°C ~ 70°C
G		12H	
H		O-film	
J	IPS		
K	VA		
L	TN	6H	Automobile Grade -30°C ~ 80°C
M		12H	
N		O-film	
P	IPS		
Q	VA		

Note: TN = Twisted Nematic Panel, IPS = In-Plane Switching Panel, VA = Vertical Alignment Panel

First FC components