Winstar Display Co., LTD
華凌光電股份有限公司
WEB: http://www.winstar.com.tw E-mail: winstar@winstar.com.tw

SPECIFICATION

MODULE NO.: WF62-640320AD#004-FC

General Specifications

Item	Dimension	Unit
Size	6.2	inch
Dot Matrix	640 x 320	dots
Module dimension	170.32 x 88.3 x 5.3	mm
Active area	140 x 70	mm
Dot pitch	0.21875 x 0. 21875	mm
LCD type	TFT,Normally Black,Transmissive	
View Direction	Wide View	
Gray Scale	16 Gray scale (4BPP)/ 4 Gray scale (2BPP)/ 2 Gray scale (1BPP)	
Driver IC	ST7511U	
Backlight Type	LED, Normally White	
With/Without TP	Without TP	
Surface	Glare	

* Mono tone slight changed by temperature and driving voltage.

WINSTAR DISPLAY CO.,LTD.

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	℃
Storage Temperature	TST	-30	—	+80	℃

Electrical Characteristics

Operating conditions:

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage For LCM	VDD	—	3.0	3.3	3.6	V
Supply Current For LCM	IDD	—	—	25	38	mA
Power Consumption	—	—	—	83	137	mW

WINSTAR DISPLAY CO., LTD.


Interface

LCM PIN Definition

Pin	Symbol	Function
1	GND	System ground
2	VDD	Power Supply : +3.3V
3	NC	No connect
4	A0	Data/Command select
5	/WR(R/W)	Write strobe signal
6	/RD(E)	Read strobe signal
7	DB0	Data bus
8	DB1	Data bus
9	DB2	Data bus
10	DB3	Data bus
11	DB4	Data bus
12	DB5	Data bus
13	DB6	Data bus
14	DB7	Data bus
15	/CS	Chip select
16	/RESET(RSTB)	Hardware reset
17	IF0	Mode select
18	IF1	
19	NC	No connect
20	NC	No connect
21	NC	No connect
22	NC	No connect

WINSTAR DISPLAY CO.; LTD.

Contour Drawing



PIN	Finction
1	GND
2	VDD
3	NC
4	D/C#(A0)
5	WR#(RW#)
6	RD#(E)
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4

PIN	Finction
11	DB4
12	DB5
13	DB6
14	DB7
15	CS#
16	Reset(RSTB)
17	IF0
18	IF1
19	NC
20	NC
21	NC
22	NC

The non-specified tolerance of dimension is ±0.3mm.

WINSTAR DISPLAY CO.,LTD.